

HYDROMA, SPOL. S R.O.

VLČNOVSKÁ 2477, 688 01 UHERSKÝ BROD, CZECH REPUBLIC

TEL.: +420 572 637796 , TEL./FAX +420 572 637729

e-mail: hydroma@hydroma.cz



CSU 16 - 20 - 25 - 35 - 45 - 50 - 53

OBJEDNACÍ KÓD

CSU 25 T1 F1 03

SÉRIE
PRODUCT SERIES

TYP
TYPE

16
20
25
35
45
50
53

3 - CESTNÝ TERMOREGULAČNÍ VENTIL

3 WAYS TEMPERATURE REGULATOR

INIZIO APERTURA

COMPLETA APERTURA

OPENING TEMP.

MAX FLOW TO COOLER AT

T1	40°C	50°C
T2	55°C	65°C
T3	70°C	80°C

FILTRACE
FILTRATION (MICRON)

F1 - 5 micron fibra di vetro (solo per viscosita' fino a 100 cst)
5 micron fiber glass (viscosity up to 100 cst)

F2 - 10 micron carta
10 micron paper

F3 - 25 micron carta
25 micron paper

F4 - 60 micron tela inox Aisi 304
60 micron Aisi 304 s.s. mesh

VOLTAGE

01 - 230V AC 50HZ 1PHASE

03 - 230-400V AC 50/60HZ 3PHASE (460V 50HZ-480V 60HZ)

04 - TENSTIONI SPECIALI - SPECIAL VOLTAGE

CARTUCCE DI RICAMBIO
SPARE PARTS CARTRIDGE

F1 - SO 5

F2 - SO 10

F3 - SO 25

F4 - SO 60

HYDROMA, SPOL. S R.O.

VLČNOVSKÁ 2477, 688 01 UHERSKÝ BROD, CZECH REPUBLIC

TEL.: +420 572 637796 , TEL./FAX +420 572 637729

e-mail: hydroma@hydroma.cz

ZÁSTAVBOVÉ ROZMĚRY

EMMEGI
HYDRA-TECHNICAL

Pressacavo Pg 11
Cable gland Pg 11

N.4 Asole ø1x15
Slotted holes

* Versione senza carena disponibile a richiesta.
* Version without cover available on request.

Per effettuare il cablaggio elettrico togliere le viti del coperchio e sollevarlo per accedere al motore
For connection of electric wiring open the top cover in order to reach the motor

CSU 16-20-25-35-45-50-53

DIMENSIONI DI INGOMBRO - TOTAL DIMENSIONS

TYPE	A	B	D	E	F	G	H	L	M	N	Mot. (Kw)	A	dB(A) (1 mt)	Kg	Q _{air} (m ³ /h)	Q _{oil} (lpm)
16	316	460	423	349	316	369	157	226	360	400	0.55	0.8	61	28	360	10
20	316	465	436	345	315	365	149.5	225	280	320	0.75	1.15	66	33	360	30
25	376	465	484	405	360	425	180	295	280	320	0.75	1.15	67	35	540	30
35	440	475	560	467	420	487	210	354	290	330	0.75	1.15	71	40	950	30
45/50	534	485	654	562	515	582	257.5	450	300	340	0.75	2.05	75	50	2050	30
53	671	480	800	699	610	719	305	544	380	420	1.6	2.2	85	70	5600	60

Le dimensioni e le caratteristiche tecniche non sono impegnative. Over-all dimensions and technical characteristics are not binding.

HYDROMA, SPOL. S R.O.

VLČNOVSKÁ 2477, 688 01 UHERSKÝ BROD, CZECH REPUBLIC

TEL.: +420 572 637796 , TEL./FAX +420 572 637729

e-mail: hydroma@hydroma.cz



CSU 16-20-25-35-45-50-53

VÝKONOVÝ DIAGRAM

